



NOTE:
 PRESSED STEEL CASING WITH A BLACK FERRITIC FINISH. ALSO UTILISES A BLACK PLASTIC HANDLE AND IS SUPPLIED WITH A BLACK STEEL FIXING PLATE.

STRIKER PIN - 9301/101 TO BE USED

RECOMMENDED SCREW TORQUE ON MOUNTING LATCH 6-8 Nm

RECOMMENDED STRIKER BOLT LOAD ON MOUNTED LATCH 11.5kg

M6 x 1.0 CLASS 8.8 CSK SCREWS OR BETTER MUST BE USED TO SECURE LATCH MECHANISM TO CAB DOOR

GENERAL TOLERANCES ON LENGTHS	
0.5 - 6 ± 0.1mm	
6 - 30 ± 0.2mm	
30 - 120 ± 0.3mm	
120 - 400 ± 0.5mm	
400 - 1000 ± 0.8mm	
1000 - 2000 ± 1.2mm	
2000 - 4000 ± 2.0mm	

ALBERT JAGGER LTD
 GREEN LANE
 WALSALL
 WEST MIDLANDS
 WS2 8HG

PHONE: 01922 471000
 FAX: 01922 648021

THIS DRAWING & THE DESIGN SHOWN ARE THE PROPERTY OF ALBERT JAGGER LTD AND MUST NOT BE USED OR COPIED BY A THIRD PARTY WITHOUT PERMISSION

DRAWN BY
 U.F

CHECKED BY
 A.P



SCALE
 1:1.5

MATERIAL
 SEE NOTE

MASS
 0.380kg

FINISH
 SEE NOTE

Date
 15/12/2017

ALL DIMS IN MM UNLESS STATED DO NOT SCALE

A3

1	VALIDATION COMPLETE	15/08/17	A.P
REV	DESCRIPTION	DATE	APPROVED



ROLL OVER' ROTOR LATCH - RH

9310-011

Edition	Sheet
1	1 / 1